

High Shear Dispersing Emulsifier

Description

Stepless speed change, equipped with two working heads, capable of meeting the different processing capacities of the laboratory. The utility model benefits from low noise, convenient speed regulation, wide processing range, stable operation and convenient cleaning.


Applicable

Emulsification, dispersion, homogenization, liquid / liquid mixing, etc.



F18

High Shear Dispersing Emulsifier



Order

10020

Optional Agitator

Model	F18
Motor power	200W
Power supply	220V, 50Hz
Working capacity (H ₂ O)	100~2000mL
Maximum working viscosity	8000cP
Speed range	300~23000rpm
Speed display	Scale
Speed control	Stepless
Medium-contact material	SS304
Shaft sleeve material	PTFE
Standard dispersing agitator	12G、18G
Permissible temperature range	5~40°C
Permissible humidity range	80%
Process type	Batch processing
Work frame, stand base	Standard
Overall dimensions	225×328×600
Weight	~9kg
Package	Carton



12G

18G

Biology
Pharmacy

Food

Daily Care

Chemical
Industry

New
Material



FLUKO EQUIPMENT SHANGHAI CO., LTD.
#21-22 NO. 300, Shunda Road, Jiading, 201802, Shanghai, China
Phone +86 21 230 993 68, Fax +86 21 510 103 68
sales@fluko.com, www.fluko.com