

FAR25 High Shear Dispersing Emulsifier

FLUKO®

Description

With a high speed pneumatic motor, the structure is light, safe, and easy to operate. Suitable for explosive or dangerous areas of experimental work. Compatible with FA25 series agitators.

Applicable

The utility model is suitable for dispersing, emulsifying, homogenizing and mixing containing machines, solvents or other inflammable and explosive materials.



FAR25

High Shear Dispersing Emulsifier



Order

Model	FAR25
Motor power	670W
Air consumption	0.8m ³ /min
Ventilation pressure	0~6bar
Working capacity (H ₂ O)	0.2~5000mL
Maximum working viscosity	5000cP
Rotation speed range (no-load)	14000rpm
Speed control	Stepless
Medium-contact material	SS316L
Shaft sleeve material	PTFE
Standard agitator	25F
Permissible temperature range	5~40°C
Permissible humidity	80%
Process type	Batch processing
Work frame, stand base	Standard
Overall dimensions	215×310×730
Weight	~7kg
Package	Carton

6224052

FAR25
670W
0.8m ³ /min
0~6bar
0.2~5000mL
5000cP
14000rpm
Stepless
SS316L
PTFE
25F
5~40°C
80%
Batch processing
Standard
215×310×730
~7kg
Carton

Optional Agitators

Order #>Model		
		
001	011	021
6G	8G	10G
		
031	032	041
18G	18F	20DG
		
042	051	052
20DF	25G	25F
		
053	054	055
25DG	25DF	25J
		
056	057	058
25JQ	25JX	25T1
		
059	060	061
25T2	25T3	25T4
		
062	063	
25T5	25T6	



Pneumatic explosion-proof

Biology
Pharmacy

Food

Daily Care

Chemical
Industry

New
Material

FLUKO EQUIPMENT SHANGHAI CO., LTD.
#21-22 NO. 300, Shunda Road, Jiading, 201802, Shanghai, China
Phone +86 21 230 993 68, Fax +86 21 510 103 68
sales@fluko.com , www.fluko.com

