

FA30+FA30D

High Shear Dispersing Emulsifier

FLUKO®

Description

High power, high speed original motor, rotation speed up to 25000rpm, tip speed up to 35 m/s, and the maximum batch processing capacity is 10000ml. High torque design with choices of agitators. Compatible with the FA25 type agitators. Modular structure of the whole machine, easy to operate.

Applicable

Suitable for dispersing, homogenizing, emulsifying, mixing and crushing with high fineness. Quick and Effective.



FA30+FA30D

High Shear Dispersing Emulsifier



Order #	6231111	6331111	Optional Agitators	
Model	FA30	FA30D	Order #>Model	
Motor power	1050W	1050W		
Power supply	220V, 50/60Hz	220V, 50/60Hz		
Working capacity (H ₂ O)	0.2~10000mL	0.2~10000mL		
Maximum working viscosity	8000cP	8000cP		
Rotation speed range	3500~25000rpm	3500~25000rpm		
Speed display	Scale	Digital display	111	121
Speed control	Stepless	Stepless	30G	30F
Medium-contact material	SS316L	SS316L		
Shaft sleeve material	PTFE	PTFE		
Standard agitator	30G	30G		
Permissible temperature range	5~40°C	5~40°C		
Permissible humidity	80%	80%		
Work frame, stand base	Standard	Standard		
Overall dimensions	215×310×730	215×310×730		
Weight	~9.8kg	~9.8kg	112	122
Package	Carton	Carton	30DG	30DF



Biology
Pharmacy

Food

Daily Care

Chemical
Industry

New
Material



FLUKO EQUIPMENT SHANGHAI CO., LTD.
#21-22 NO. 300, Shunda Road, Jiading, 201802, Shanghai, China
Phone +86 21 230 993 68, Fax +86 21 510 103 68
sales@fluko.com, www.fluko.com