

FA90C

High Shear Dispersing Emulsifier

FLUKO®

Description

Designed for pilot production, analog production and factory small batch production with a maximum capacity of 50L. The standard agitator has dispersion, emulsification and homogeneous balanced design, providing efficient fine mixing ability. The machine offers frequency conversion, speed display, manual hydraulic lifting and other functions.


Applicable

Pilot for high efficiency stirring, dispersing, homogenizing, emulsifying, strong mixing, solid-liquid mixing and other processes.



FA90C

High Shear Dispersing Emulsifier



Order

6292242

Model	FA90C-242-M
Motor power	1500W
Power supply	220V , 50Hz
Working capacity(H ₂ O)	10-50L
Maximum working viscosity	8000cP
Speed range	600-3600rpm
Speed display	Digital display
Speed control	Frequency control
Medium-contact material	SS316L
Standard dispersing agitator	90F
Permissible temperature range	5-40°C
Permissible humidity range	80%
Protection grade for motor hood	IP54
Inverter	Standard
Overload protection	Yes
Process type	Batch processing
Work frame, stand base	Manual lifting
Work frame, stand base material	SS304
Lifting range	450
Overall dimensions	800 × 650 × 1000
Weight	~50kg
Package	Wooden case

Biology
Pharmacy

Food

Daily Care

Chemical
Industry

New
Material



FLUKO EQUIPMENT SHANGHAI CO., LTD.
 #21-22 NO. 300, Shunda Road, Jiading, 201802, Shanghai, China
 Phone +86 21 230 993 68, Fax +86 21 510 103 68
sales@fluko.com , www.fluko.com